

Your contact for special steels

Steel Strip and Sheets

For us, steel expertise means that we offer you, the customer, the best possible solution for your requirements. We specialize in delivering smaller quantities to our customers. This allows our customers to benefit from a high degree of flexibility in order to implement their projects and orders more easily and cost-effectively.

We see ourselves as a competent partner that guarantees reliable delivery, high quality and high availability. We are certified according to the SN EN ISO 9001:2015 standard. Our employees are PSCR VDA QMC licensed by Tüv Süd, ensuring the highest standards of expertise and professionalism.

Please contact us if you cannot find the product you are looking for - we will be happy to check our options and consult you!

mimeta

Steel strip and Sheets

>> hot rolled / re-rolled	Grades	Norm
soft steels for cold forming	DD11 -DD14	EN 10111
non-alloy structural steel	S235JR, S355J2	EN 10025
high-yield structural steel for cold forming	S315MC - S700MC	EN 10149
tempering steel	51CrV4, 42CrMo4	EN 10083
case-hardened steel	C10E, 16MnCr5, 20MnCr5	EN 10084
<i>Other material grades on request</i>		

Dimensional range	Thickness	Width	Length
Slit strip	1,00 - 13,0 mm	8,00 – 600 mm	
Blank	200 – 6000 mm	200 – 1500 mm	200 – 6000 mm

>> cold rolled / re-rolled	Grades	Norm
soft steels for cold forming	DC01 - DC07	EN 10130
high-yield structural steel for cold forming	HC260LA - HC420LA	EN 10268
<i>Other material grades on request</i>		

Dimensional range	Thickness	Width	Length
Slit strip	0,40 – 2,99 mm	8,00 – 600 mm	
Blank	0,40 – 2,99 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,40 – 2,99 mm	600 – 1500 mm	
Sheet	0,40 – 2,99 mm	600 – 1500 mm	1000 – 6000 mm
<i>Other material grades on request</i>			

>> electrogalvanized [ZE]	Grades	Norm
soft steels for cold forming	DC01+ZE - DC07+ZE	EN 10152
high-yield structural steel for cold forming	HC260LA+ZE - HC420LA+ZE	EN 10268
<i>Other material grades on request</i>		

Dimensional range	Thickness	Width	Length
Slit strip	0,40 – 2,99 mm	8,00 – 600 mm	
Blank	0,40 – 2,99 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,40 – 2,99 mm	600 – 1500 mm	
Sheet	0,40 – 2,99 mm	600 – 1500 mm	1000 – 6000 mm
<i>Other material grades on request</i>			

>> hot-dip galvanized [Z]	Grades	Norm
soft steels for cold forming	DX51D+Z - DX57D+Z	EN 10346 EN 10327
structural steel	S220GD+Z - S550GD+Z	EN 10346 EN 10326
high-yield structural steel for cold forming	HX260LAD+Z - HX500LAD+Z	EN 10346 EN 10292
<i>Other material grades on request a. o. HCT / HDT Multiphase steels</i>		

Dimensional range	Thickness	Width	Length
Slit strip	0,20 – 3,00 mm	8,00 – 600 mm	
Blank	0,35 – 3,00 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,35 – 3,00 mm	600 – 1500 mm	

>> galvanized [ZF]	Grades	Norm
soft steels for cold forming	DX51D+ZF - DX57D+ZF	EN 10346 EN 10327
structural steel	S220GD+ZF - S550GD+ZF	EN 10346 EN 10326
high-yield structural steel for cold forming	HX260LAD+ZF - HX500LAD+ZF	EN 10346 EN 10292
<i>Other material grades on request a. o. HCT / HDT Multiphase steels</i>		

Dimensional range	Thickness	Width	Length
Slit strip	0,40 – 3,00 mm	8,00 – 600 mm	
Blank	0,40 – 3,00 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,40 – 3,00 mm	600 – 1500 mm	

>> Galfan [ZA]	Grades	Norm
soft steels for cold forming	DX51D+ZA - DX57D+ZA	EN 10346 EN 10327
structural steel	S220GD+ZA - S550GD+ZA	EN 10346 EN 10326
high-yield structural steel for cold forming	HX260LAD+ZA - HA500LAD+ZA	EN 10346 EN 10292
<i>Other material grades on request a. o. HCT / HDT Multiphase steels</i>		

Dimensional range	Thickness	Width	Length
Slit strip	0,35 – 3,00 mm	8,00 – 600 mm	
Blank	0,35 – 3,00 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,35 – 3,00 mm	600 – 1500 mm	
Sheet	0,35 – 3,00 mm	500 – 1500 mm	1000 – 6000 mm

Other dimensions are possible upon request

>> Aluzinc- / Galvalume [AZ]		Grades	Norm
soft steels for cold forming		DX51D+AZ - DX54D+AZ	EN 10346 EN 10327
structural steel		S220GD+AZ - S550GD+AZ	EN 10346 EN 10326
<i>Other material grades on request</i>			
Dimensional range	Thickness	Width	Length
Slit strip	0,35 – 2,00 mm	8,00 – 600 mm	
Blank	0,35 – 2,00 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,35 – 2,00 mm	600 – 1500 mm	
Sheet	0,35 – 2,00 mm	500 – 1500 mm	1000 – 6000 mm
<i>Other dimensions are possible upon request</i>			

>> Hot-dip aluminized [AS]		Grades	Norm
soft steels for cold forming		DX51D+AS - DX57D+AS	EN 10346 EN 10327
structural steel		S250GD+AS - S350GD+AS	EN 10346 EN 10326
<i>Other material grades on request</i>			
Dimensional range	Thickness	Width	Length
Slit strip	0,35 – 3,00 mm	8,00 – 600 mm	
Blank	0,35 – 3,00 mm	200 – 1500 mm	200 – 6000 mm
Strip	0,35 – 3,00 mm	600 – 1500 mm	
Sheet	0,35 – 3,00 mm	600 – 1500 mm	1000 – 6000 mm
<i>Other dimensions are possible upon request</i>			

>> colour coated material		Grades	Norm
soft steels for cold forming		DC01 - DC04, DC01+ZE - DC04+ZE, DX51D+Z - DX56D+Z, DX51D+ZA - DX56D+ZA	EN 10169 EN 10130
structural steel		S250GD+Z - S320GD+Z	EN 10169 EN 10346
<i>Other material grades on request</i>			
Dimensional range	Thickness	Width	Length
Slit strip	0,35 – 2,00 mm	8,00 – 600 mm	
Blank	0,35 – 2,00 mm	200 – 1400 mm	200 – 6000 mm
Strip	0,35 – 2,00 mm	600 – 1400 mm	
Sheet	0,35 – 2,00 mm	600 – 1400 mm	1000 – 6000 mm
<i>Other dimensions are possible upon request</i>			

Contact

steel@mimeta.ch – T: +41 21 654 40 34 or +41 21 654 40 37

Address

Mimeta Ltd - Stettbachstrasse 6 - 8600 Dübendorf – Switzerland

Headquarters – Avenue de Béthusy 54 – 1012 Lausanne – Switzerland - UID - CHE - 460.710.739